



**CONTERA  
REDONDA  
INTERIOR  
ESTRIADA**

Referencia	Ø Ext.	Ø Int.	B	C	GROSOR TUBO
<b>STR-IP-12A</b>	12	8-10	9	5.5	1.0-2.0
<b>STR-IP-14</b>	14	10-12	14	4	1.0-2.0
<b>STR-IP-16</b>	16	12-14	14	5	1.0-2.0
<b>STR-IP-18</b>	18	14-16	14	5	1.0-2.0
<b>STR-IP-20</b>	20	16-18	16	6	1.0-2.0
<b>STR-IP-22</b>	22	18-20	17	6	1.0-2.0
<b>STR-IP-23A</b>	23	19-21	17.5	10	1.0-2.0
<b>STR-IP-25</b>	25	21-23	19	8	1.0-2.0
<b>STR-IP-26A</b>	26	22-24	18	9	1.0-2.0
<b>STR-IP-27A</b>	27	21-25	19	6.5	1.0-3.0
<b>STR-IP-28</b>	28	24-26	19	6	1.0-2.0
<b>STR-IP-30</b>	30	26-28	19	8	1.0-2.0
<b>STR-IP-32</b>	32	28-30	19	8	1.0-2.0
<b>STR-IP-35</b>	35	31-33	18	8	1.0-2.0
<b>STR-IP-38</b>	38	34-36	18	5	1.0-2.0
<b>STR-IP-40</b>	40	36-38	19	7	1.0-2.0
<b>STR-IP-42A</b>	42	36.5-40	19	6	1.0 - 2.75
<b>STR-IP-45</b>	45	41-43	19	5	1.0-2.0
<b>STR-IP-48A</b>	48	42.5-46	19	6	1.0-2.75
<b>STR-IP-50</b>	50	46-48	22	7	1.0-2.0
<b>STR-IP-55A</b>	55	49.5-53	19	6	1.0-2.75

<b>STR-IP-60</b>	60	56-58	17	5	1.0-2.0
<b>STR-IP-63A</b>	63	58-61	19	5.5	1.0-2.5
<b>STR-IP-70A</b>	70	64-68	18.5	6.5	1.0-3.0
<b>STR-IP-76A</b>	76	70.5-74	19.5	5.5	1.0-2.75
<b>STR-IP-76AX3</b>	76	67-70	19.5	5.5	3.0-4.5
<b>STR-IP-80A</b>	80	73-78	18.5	6.5	1.0-3.5
<b>STR-IP-85A</b>	85	79-82	21	6.5	1.0-3.0
<b>STR-IP-90A</b>	90	83-88	17	5	1.0-3.5
<b>STR-IP-100A</b>	100	96-98	17	5	1.0-2.0
<b>STR-IP-100AX3</b>	100	92.5-95.5	17	5	2.25-3.75
<b>STR-IP-102A</b>	102	96-98	17	5	2.0-3.0
<b>STR-IP-110A</b>	110	102-106	21	6	2.0-4.0
<b>STR-IP-114A</b>	114	106-110	20	6	2.0-4.0
<b>STR-IP-120A</b>	120	112-116	20.5	6	2.0-4.0